

KEMSAN SFK33 MODEL TRANSFORMER TEST CONVERTER

Microprocessor Controlled

3 Phase Input 3Phase Output



- By using advanced Digital Control Methods, complete sine waveform at the output under linear and non-linear load. (THD lower than %2)
- DSP Microprocessor structure
- Static structure, PWM controlled inverter with IGBT
- Output Transformer with galvanic isolation
- Monitoring and controlling over ModBus(RTU) (optional)
- Monitoring and controlling over CANBUS(RTU) (optional)
- Monitoring and controlling over TCP/IP network with the SNMP board (optional)
- Communication through RS232/RS422/RS485 (optional)
- 4-20mA, 0-10V Analog output for PLC (optional)
- Real-time monitoring and control of Frequency Converters over the internet using an internet connected PC with static IP number (optional) 100 warning lists and for each warning detailed warning report
- Batteries can be connected (optional)
- 128x64 LCD Control Board

POWER (kVA)		100	150	200	300	400	500	600	800
INPUT	Voltage	220-230-254/ 380-400-440VAC ±% 15 (3 Phase + Neutral/ Input Voltage Optional)							
	Frequency	50Hz/60Hz ± %5 (Input Frequency Optional)							
	Protection	Adjustable voltage and current restrictions + Fuse							
	Input Power Factor	> 0,9							
	Total Harmonic Distortion	< %6 (12 Pulse)							
OUTPUT	Voltage	Adjustable in the range of 20-440 ±%2 (Output Voltage Optional)							
	Frequency	50/60/150/200 Hz ±%0,2 (Output Frequency Optional)							
	Efficiency	>%91 (Full Load)							
	Total Harmonic Distortion	< %2							
	Power Factor	0.8 Inductive-Capacitive							
	Overload	Under the load higher than %125(optional) for 10 second system automatic shutdown							
	Voltage Protection	Range of operating voltage can adjustable from the LCD Control Board, inverter shuts down outside the operating voltage							
	Thermal Protection	IGBT Cooler and Output Transformer Thermal Protection							
	Load Crest Factor	3:1							
BATT.	Voltage	Designs without batteries are standart.(Designs with batteries should be notified with the order)							
	Number Of Batteries	Optional							
	Duration	Optional							
PHYSICAL SPECIFICATIONS	AMBIENT	Temperature	0-40 °C						
		Relative Humidity	%0-95 (non-condensing)						
		Acoustic Noise	<68 dB (A) (1 meter)	<70 dB (A) (1 meter)	<72 dB (A) (1 meter)	<78 dB (A) (1 meter)			
		Operation Altitude	2000 m.						
	Protection Class	IP20							
	Dimensions(mm)	W=1610, D=830, H=1900		W=2020-3620, D=1030, H=1900			W=4020-4820, D=1030, H=1900		
	Weight Without Batteries (Kg)	1280	1630	2450	3340	4250	5225	6160	7250
GENERAL SPECIFICATIONS	Display	128x64 LCD Board with Line,Charge,Inverter Warning LEDs							
	Warnings	Can hold 100 warning list (name,date,time) for each warning detailed report (23 system information stored)							
	Working System	Static, Converter with IGBT switches							
	Working Technique	Advanced High Frequency PWM, IGBT Technology							
	Communication	Server,Terminal Programmes, communication with RS232/RS422/RS485(optional), 4-20mA and 0-10V Analog output for PLC (optional), Observing and controlling over ModBus(RTU) (optional), Observing and controlling over CANBUS (RTU) (optional), Remote monitoring and control by providing TCP / IP number with SNMP card (optional).							
	Output isolation	High Insulation with Isolated Output Transformer							
	Overcurrent Protection	Under the load higher than %125(optional) for 10 seconds system will automatic shutdown, Fuse							
 KEŞİNTİSİZ GÜCÜN KAYNAĞI		KAYNAK ELEKTRONİK MAKİNA SAN. TİC. LTD. ŞTİ. Baksan Sanayi Sitesi Çıraklık Okulu Arkası 124/ 8 ESKİŞEHİR Tel : 0 (222) 340 45 45 pbx Fax : 0 (222) 340 45 42 www.kemsan.com.tr e-mail : info@kemsan.com.tr							